


Product description

MN1,5E32-200-4P-50-TM-SS

Pos.no	Description	Item no	Qty.	UP / €	TP / €
1	Close-coupled electric pump according to EN 733 (DIN 24255)				
2	Centrifugal pump: MN1,5E32-200-4P-50-TM-SS		1	Price on req.	Price on req.
3	<p>Pump bodies</p> <p>Close-coupled electric pumps in compliance with EN 733 - DIN 24255 standards coupled to IEC standard electric motors through rigid coupling.</p> <p>Duty point</p> <p>Flow : / Head :</p> <p>Pump operating data</p> <p>Impeller diameter : 205 mm / Speed : 1.450 1/min</p> <p>Flow : / Head :</p> <p>Shaft power P2 : / Efficiency :</p> <p>Head (Q = 0) : 14,93 m</p> <p>Pump body : Cast iron</p> <p>Impeller : Stainless steel</p> <p>Wear ring : Cast iron</p> <p>Support : Cast iron</p> <p>Coupling : Cast iron</p> <p>Shaft : Stainless steel</p> <p>Max. solid contents : 40 g/m³</p> <p>Max. water temperature : 90 °C</p> <p>Max. running time with Q=0 : 2 min</p>				
4	Motor: IEC 1,5 - 4		1		
5	<p>Electric motor</p> <p>Three-phase IE3 asynchronous squirrel cage motor.</p> <p>Casing : Aluminium</p> <p>Protection : IP 55</p> <p>Insulation class : F</p> <p>Number of startings : max 14</p> <p>Max environment temperature : 40 °C</p> <p>Max altimetric level : 1000 m</p> <p>Weight : 16 kg</p> <p>Frequency : 50 Hz</p> <p>N. poles : 4</p> <p>P2 : 1,1 kW</p> <p>U : 230 V</p> <p>In 1/1 : 2,52 A</p> <p>EFF : 84,1 %</p> <p>CosPhi : 0,75</p>				
6	Shaft seal: Mechanical seal		1		
7	<p>Cover : Cast iron</p> <p>Spacer : Stainless steel</p> <p>Seal face : Graphite</p> <p>Seat : Ceramic</p> <p>Seal ring : NBR</p> <p>Spring : AISI 304 stainless steel</p>				

Technical data

MN1,5E32-200-4P-50-TM-SS



Operating data specification	
Capacity	
Head	
Fluid	Pure water
Type of installation	<Single head pump>

Pump operating data	
Design	MN1,5E32-200-4P-50-TM-SI
Impeller Ø	205 mm
Speed	1.450 1/min
Flow	
Head	
Shaft power P2	
Efficiency	
Head (Q=0)	14,9 m
Non return valve loss	

Electric motor technical data	
Design	IEC 1,5 - 4
Rated power	1,1 kW
Frequency	50 Hz
Number of poles	4
Nominal speed	1.450 1/min
Rated voltage	3~ 230 V
Starting mode	Direct starting
Rated current	2,52 A
Insulation class	F
Degree of protection	IP 55

Use limits	
Max N° startings/hour	14
Max. running time with Q=0	2 min
Max. solids contents	40 g/m ³
Max. pumped liquid temperature	90 °C
Maximum density	998 kg/m ³
Maximum viscosity	1 mm ² /s

Materials	
Pump body	Cast iron
Impeller	Stainless steel
Wear ring	Cast iron
Support	Cast iron
Coupling	Cast iron
Shaft	Stainless steel

Shaft seal	
Cover	Cast iron
Spacer	Stainless steel
Seal face	Graphite
Seat	Ceramic
Seal ring	NBR
Spring	AISI 304 stainless steel




Dimensions in		mm		Total weight		55 kg	
a	80	Da1	165	E	56	m1	100
A	140	Da2	125	G1	135	m2	70
AB	180	Da3	18	G2	143	n1	240
b	50	Dm1	140	H	90	n2	190
B	100	Dm2	100	h1	160	s1	14
BB	140	Dm3	18	h2	180	x	4
C	265	DNa	50	K	10	y	4
D	140	DNrr	32	L	310		

Performance curves

MN1,5E32-200-4P-50-TM-SS

Performances				
Speed		1.450 1/min	Density	998 kg/m ³
Flow	Min.	4,5 m ³ /h	Viscosity	1 mm ² /s
	Max.	18 m ³ /h		
Efficiency	Max.	16,3 m ³ /h	Temperature	20 °C
				Tolerances



Types of installation

MN1,5E32-200-4P-50-TM-SS



Total weight		55 kg		Dimensions in mm	
a	80	h2	180		
A	140	K	10		
AB	180	L	310		
b	50	m1	100		
B	100	m2	70		
BB	140	n1	240		
C	265	n2	190		
D	140	s1	14		
Da1	165	x	4		
Da2	125	y	4		
Da3	18				
Dm1	140				
Dm2	100				
Dm3	18				
DNa	50				
DNm	32				
E	56				
G1	135				
G2	143				
H	90				
h1	160				