


Product description

MN20E80-315-4P-50-TM-SS

Pos.no	Description	Item no	Qty.	UP / €	TP / €
1	Close-coupled electric pump according to EN 733 (DIN 24255)				
2	Centrifugal pump: MN20E80-315-4P-50-TM-SS		1	Price on req.	Price on req.
3	<p>Pump bodies</p> <p>Close-coupled electric pumps in compliance with EN 733 - DIN 24255 standards coupled to IEC standard electric motors through rigid coupling.</p> <p>Duty point</p> <p>Flow : / Head :</p> <p>Pump operating data</p> <p>Impeller diameter : 278 mm / Speed : 1.450 1/min</p> <p>Flow : / Head :</p> <p>Shaft power P2 : / Efficiency :</p> <p>Head (Q = 0) : 28,27 m</p> <p>Pump body : Cast iron</p> <p>Impeller : Stainless steel</p> <p>Wear ring : Cast iron</p> <p>Support : Cast iron</p> <p>Coupling : Cast iron</p> <p>Shaft : Stainless steel</p> <p>Max. solid contents : 40 g/m³</p> <p>Max. water temperature : 90 °C</p> <p>Max. running time with Q=0 : 2 min</p>				
4	Motor: IEC 20 - 4		1		
5	<p>Electric motor</p> <p>Three-phase IE3 asynchronous squirrel cage motor.</p> <p>Casing : Cast iron</p> <p>Protection : IP 55</p> <p>Insulation class : F</p> <p>Number of startings : max 14</p> <p>Max environment temperature : 40 °C</p> <p>Max altimetric level : 1000 m</p> <p>Weight : 141 kg</p> <p>Frequency : 50 Hz</p> <p>N. poles : 4</p> <p>P2 : 15 kW</p> <p>U : 400 V</p> <p>In 1/1 : 27,3 A</p> <p>EFF : 92,1 %</p> <p>CosPhi : 0,86</p>				
6	Shaft seal: Mechanical seal		1		
7	<p>Cover : Cast iron</p> <p>Spacer : Stainless steel</p> <p>Seal face : Graphite</p> <p>Seat : Ceramic</p> <p>Seal ring : NBR</p> <p>Spring : AISI 304 stainless steel</p>				

Technical data

MN20E80-315-4P-50-TM-SS



Operating data specification	
Capacity	
Head	
Fluid	Pure water
Type of installation	<Single head pump>

Pump operating data	
Design	MN20E80-315-4P-50-TM-SS
Impeller Ø	278 mm
Speed	1.450 1/min
Flow	
Head	
Shaft power P2	
Efficiency	
Head (Q=0)	28,3 m
Non return valve loss	

Electric motor technical data	
Design	IEC 20 - 4
Rated power	15 kW
Frequency	50 Hz
Number of poles	4
Nominal speed	1.450 1/min
Rated voltage	3~ 400 V
Starting mode	Direct starting
Rated current	27,3 A
Insulation class	F
Degree of protection	IP 55

Use limits	
Max N° startings/hour	14
Max. running time with Q=0	2 min
Max. solids contents	40 g/m ³
Max. pumped liquid temperature	90 °C
Maximum density	998 kg/m ³
Maximum viscosity	1 mm ² /s

Materials	
Pump body	Cast iron
Impeller	Stainless steel
Wear ring	Cast iron
Support	Cast iron
Coupling	Cast iron
Shaft	Stainless steel

Shaft seal	
Cover	Cast iron
Spacer	Stainless steel
Seal face	Graphite
Seat	Ceramic
Seal ring	NBR
Spring	AISI 304 stainless steel




Dimensions in		mm		Total weight		247 kg	
a	125	Da1	220	E	108	m1	160
A	254	Da2	180	G1	217	m2	120
AB	315	Da3	18	G2	238	n1	400
b	80	Dm1	200	H	160	n2	315
B	254	Dm2	160	h1	250	s1	19
BB	305	Dm3	18	h2	315	x	8
C	542	DNa	100	K	15	y	8
D	265	DNrr	80	L	457		

Performance curves

MN20E80-315-4P-50-TM-SS

Performances				
Speed		1.450 1/min	Density	998 kg/m ³
Flow	Min.	60 m ³ /h	Viscosity	1 mm ² /s
	Max.	183 m ³ /h	Temperature	20 °C
Efficiency	Max.	124 m ³ /h	Tolerances	ISO 9906 Grade 3B



Types of installation

MN20E80-315-4P-50-TM-SS



Total weight		247 kg		Dimensions in mm	
a	125	h2	315		
A	254	K	15		
AB	315	L	457		
b	80	m1	160		
B	254	m2	120		
BB	305	n1	400		
C	542	n2	315		
D	265	s1	19		
Da1	220	x	8		
Da2	180	y	8		
Da3	18				
Dm1	200				
Dm2	160				
Dm3	18				
DNa	100				
DNm	80				
E	108				
G1	217				
G2	238				
H	160				
h1	250				