


Product description

MN50E80-200-2P-50-TM-SS

Pos.no	Description	Item no	Qty.	UP / €	TP / €
1	Close-coupled electric pump according to EN 733 (DIN 24255)				
2	Centrifugal pump: MN50E80-200-2P-50-TM-SS		1	Price on req.	Price on req.
3	<p>Pump bodies</p> <p>Close-coupled electric pumps in compliance with EN 733 - DIN 24255 standards coupled to IEC standard electric motors through rigid coupling.</p> <p>Duty point</p> <p>Flow : / Head :</p> <p>Pump operating data</p> <p>Impeller diameter : 197 mm / Speed : 2.900 1/min</p> <p>Flow : / Head :</p> <p>Shaft power P2 : / Efficiency :</p> <p>Head (Q = 0) : 51,37 m</p> <p>Pump body : Cast iron</p> <p>Impeller : Stainless steel</p> <p>Wear ring : Cast iron</p> <p>Support : Cast iron</p> <p>Coupling : Cast iron</p> <p>Shaft : Stainless steel</p> <p>Max. solid contents : 40 g/m³</p> <p>Max. water temperature : 90 °C</p> <p>Max. running time with Q=0 : 2 min</p>				
4	Motor: IEC 50 - 2		1		
5	<p>Electric motor</p> <p>Three-phase IE3 asynchronous squirrel cage motor.</p> <p>Casing : Cast iron</p> <p>Protection : IP 55</p> <p>Insulation class : F</p> <p>Number of startings : max 5</p> <p>Max environment temperature : 40 °C</p> <p>Max altimetric level : 1000 m</p> <p>Weight : 259 kg</p> <p>Frequency : 50 Hz</p> <p>N. poles : 2</p> <p>P2 : 37 kW</p> <p>U : 400 V</p> <p>In 1/1 : 62,6 A</p> <p>EFF : 93,7 %</p> <p>CosPhi : 0,91</p>				
6	Shaft seal: Mechanical seal		1		
7	<p>Cover : Cast iron</p> <p>Spacer : Stainless steel</p> <p>Seal face : Graphite</p> <p>Seat : Ceramic</p> <p>Seal ring : NBR</p> <p>Spring : AISI 304 stainless steel</p>				

Technical data

MN50E80-200-2P-50-TM-SS



Operating data specification	
Capacity	
Head	
Fluid	Pure water
Type of installation	<Single head pump>

Pump operating data	
Design	MN50E80-200-2P-50-TM-SS
Impeller Ø	197 mm
Speed	2.900 1/min
Flow	
Head	
Shaft power P2	
Efficiency	
Head (Q=0)	51,4 m
Non return valve loss	

Electric motor technical data	
Design	IEC 50 - 2
Rated power	37 kW
Frequency	50 Hz
Number of poles	2
Nominal speed	2.900 1/min
Rated voltage	3~ 400 V
Starting mode	Direct starting
Rated current	62,6 A
Insulation class	F
Degree of protection	IP 55

Use limits	
Max N° startings/hour	5
Max. running time with Q=0	2 min
Max. solids contents	40 g/m³
Max. pumped liquid temperature	90 °C
Maximum density	998 kg/m³
Maximum viscosity	1 mm²/s

Materials	
Pump body	Cast iron
Impeller	Stainless steel
Wear ring	Cast iron
Support	Cast iron
Coupling	Cast iron
Shaft	Stainless steel

Shaft seal	
Cover	Cast iron
Spacer	Stainless steel
Seal face	Graphite
Seat	Ceramic
Seal ring	NBR
Spring	AISI 304 stainless steel




Dimensions in				mm				Total weight				329 kg			
a	125	Da1	220	E	133	m1	125								
A	318	Da2	180	G1	163	m2	95								
AB	390	Da3	18	G2	188	n1	345								
b	65	Dm1	200	H	200	n2	280								
B	305	Dm2	160	h1	180	s1	14								
BB	370	Dm3	18	h2	250	x	8								
C	675	DNa	100	K	19	y	8								
D	300	DNrr	80	L	457										

Performance curves

MN50E80-200-2P-50-TM-SS

Performances				
Speed		2.900 1/min	Density	998 kg/m ³
Flow	Min.	48 m ³ /h	Viscosity	1 mm ² /s
	Max.	224 m ³ /h	Temperature	20 °C
Efficiency	Max.	177 m ³ /h	Tolerances	ISO 9906 Grade 3B



Types of installation

MN50E80-200-2P-50-TM-SS



Total weight		329 kg		Dimensions in mm	
a	125	h2	250		
A	318	K	19		
AB	390	L	457		
b	65	m1	125		
B	305	m2	95		
BB	370	n1	345		
C	675	n2	280		
D	300	s1	14		
Da1	220	x	8		
Da2	180	y	8		
Da3	18				
Dm1	200				
Dm2	160				
Dm3	18				
DNa	100				
DNm	80				
E	133				
G1	163				
G2	188				
H	200				
h1	180				