

Company		Date	14/03/2023
Project		Item	
Pump	PCV-M 65-200Vx	Ref No.	

Liquid Data			
Liquid	Water	Density	998.3 kg/m³
Temperature	20 °C	Viscosity	1.005 mm²/s
Vapor Pressure	100 kPa	pH Value	7

Operating Point Data			
Capacity		Motor Power	22.00 kW
Head		Speed	3000 rpm
Efficiency (%)		Frequency	50 Hz
Power at Duty Point		Shut Off Head	53.83 m
Impeller Diameter	Ø 194		

Pump Data			
Design	Vertical, single stage, wide volute casing, end suction pump		
Installation	Vertical	Direction Of Rotation	Clockwise from the drive end
Discharge Flange	EN 1092 PN10	Impeller construction	
Free Passage	48 mm	Pump Weight	0 kg


Shaft Sealing			
Type			
Make			

Materials	
Volute Casing	0.6025 / GG25 / EN-GJL-250 / ASTM A48 Class 40B
Casing Cover	0.6025 / GG25 / EN-GJL-250 / ASTM A48 Class 40B
Impeller	0.6025 / GG25 / EN-GJL-250 / ASTM A48 Class 40B
Shaft	1.0503 / C45 / AISI 1045
Bearing Housing	0.6025 / GG25 / EN-GJL-250 / ASTM A48 Class 40B
Spacer Sleeve	1.0503 / C45 / AISI 1045

Company		Date	14/03/2023
Project		Item	
Pump	PCV-M 65-200Vx	Ref No.	

Operating Point Data

Capacity:	Density:	998.3 kg/m³
Head:	Motor Power:	22.00 kW
Efficiency (%):	Speed:	3000 rpm
Power at Duty Point:	Frequency:	50 Hz
Free Passage: 48 mm	Max. Shaft Power:	21.1 kW



Curves are per ISO 9906:2012 Gr 3B

